

## GO! Fish Quilt

finished size 44" x 58"



Fabric provided by P&B Textiles.

### GO!® DIES USED

- GO! Triangles in Square-4" Finished Square (55409)
- GO! Quarter Square Triangle-4" Finished Square (55316 or 55047)
- GO! Half Square Triangle-2" Finished Square (55063 or 55018)
- GO! Strip Cutter-2½" (2" Finished) (55017 or 55014)


### FABRIC REQUIREMENTS

- Fabric 1—3⅓ yards
- Fabric 2 (Variety of Greens)—3½ yards
- Fabric 3—2⅔ yards
- Batting—54" x 62"
- Backing—3 yards

### CUTTING DIRECTIONS

#### Fabric 1:

- Cut 139 pairs—"B" side triangles (55409)
- Cut 74—2" finished half square triangles
- Cut 7—2½" strips x WOF (Set aside for binding)



#### Fabric 2:

- 139—"A" center triangles (55409)

#### Fabric 3:

- 37—4" finished quarter square triangles

### SEWING DIRECTIONS

1. Lay one, 4" finished B side triangle right sides together with one, 4" finished A center triangle, so notched points align, and sew.



**NOTE:** Seam ends at point of A center triangle notch, and B side triangle point extends just beyond bottom edge of A center triangle as shown.


2. Press towards B side triangle.
3. Lay one, 4" finished B side triangle on opposite side of one, 4" finished A center triangle and sew.

4. Press towards B side triangle. Block should measure 4½" x 4½".



5. Make a total of 139, 4" Triangle in a Square (TIS) Units as shown.

6. Lay one, 2" finished half square triangle (HST) right sides together with one, 4" finished quarter square triangle (QST) as shown and sew.



7. Press towards 2" finished HST.

8. Lay one, 2" finished HST on opposite side of one, 4" finished QST and sew.



9. Press towards 2" finished HST. Flying Geese Unit should measure 2½" x 4½".



10. Make a total of 37, Flying Geese Units.

11. Lay out 4" TIS Units and Flying Geese Units according to diagram turning blocks as needed.

12. Sew blocks into vertical rows. Press seams in opposite directions.

13. Sew rows together to form the center of the quilt. Press seams all in the same direction.

## QUILTING AND FINISHING

1. Layer quilt top with batting and backing.
2. Pin or baste layers together.
3. Model was custom machine quilted.
4. Add binding, mitering the corners.